

## :: Abtönpaste Füller

pigment paste in black, blue, green and red

### CHARACTERISTICS

Solvent based Tinting Paste

- Easy tinting of fillers
- Applicable for all Carsystem 1K- and 2K Filler
- 4 different tinted pastes
- Easy to handle

### APPLICATION

A Tinting Paste for colouring the different Carsystem filler. With these 4 available colours, black, blue, green and red various fillershades can be mixed. Depending on how intense the colour should be, you can add between 1 and 5% of the tinting paste to the filler.

### PRODUCT DATA

Material Data:

- Viscosity at 20°C: liquid
- Density: 1 - 2g /cm<sup>3</sup>
- VOC-content: 2004/42/II B (b) (250) <250g/l

black: 506 g/cm<sup>3</sup>



03/2021

blue: 490 g/cm<sup>3</sup>

green: 398 g/cm<sup>3</sup>

red: 426 g/cm<sup>3</sup>

- Colour: black, blue, green, red

## HANDLING

### SURFACE:

The surface has to be clean, dry and free of grease.

### DOSAGE:

Add 1-5 % by weight in Carsystem 1K- and 2K filler

Note: The addition of the tinting paste may reduce the pot life of the filler up to max. 20%.

### REACTION TEMPERATURE:

At least +5°C

### STORAGE:

Approx. 24 month at 18 - 20° C in closed original container.

## SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions.



03/2021

In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE