

:: Acryl Thinner

acrylic thinner

CHARACTERISTICS

Acryl Thinner Standard is a mixture of organic solvents for thinning all acrylic fillers and clear coats.

APPLICATION

Universal acrylic thinner for adjustment of the spray viscosity of fillers and clear coats. The three different versions allow to use a perfect thinner depending on the working temperature and size of repair.

PRODUCT DATA

MATERIAL DATA

Colour: Colourless

Appearance: Liquid

Smell: Characteristic

Shelf life: 24 months in unopened original container

CS Acryl Thinner slow

Density: 0,89 - 0,91 g/cm³

Application: It is applied to paint large surfaces, in temperature 25 - 35°C.

CS Acryl Thinner standard

Density: 0,89 - 0,90 g/cm³

Application: It is applied to paint large surfaces, in temperature 20-25°C.

CS Acryl Thinner fast

Density: 0,87 - 0,89 g/cm³



03/2021

Application:

It is usually applied for small repairs. It can be also used by painting larger surfaces if the temperature doesn't exceed 20°C.

HANDLING

Acryl thinner is ready for use.

Follow the application guidelines as it is given in the technical data sheet of applied product.

PRECAUTIONS

Hand protection: protective gloves

Eye protection: Tightly sealed goggles

Body protection: protective clothing

DISPOSAL

Must not be disposed together with household garbage. Must not be discharged into the sewer system.

Contaminated packaging: Disposal according to official regulations.

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions.

In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising



03/2021

judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE