

:: Activator

accelerator

CHARACTERISTICS

Special additive improving drying time of fillers and clear coats. The drying time will be enhanced by approx. 15%.

It can be used only with slow and standard hardener.

Not to be used with fast and very fast hardener because the drying time will not accelerate, and it may cause defects on the coat, e.g. loss of gloss and problems with the adhesion on the filler.

APPLICATION

An additive to improve the drying time for Carsystem filler and clear coat products.

PRODUCT DATA

Color: transparent

Density: approx. 0,97 g/l

Shelf-life: 12 months

Flashpoint: + 24°C

V.O.C. < 420 g/l

HANDLING

Mixing Ratio for filler:

Filler (A) 100 (vol.)

Hardener (B) 25 (vol.)

Activator (C) 18 (vol.) / 10%

Mixing Ratio for clear coats:

Clear (A) 100 (vol.)



03/2021

Hardener (B) 50 (vol.)
Activator (C) 3 (vol.) / 2%

2004/42/IIB (D) (420) less than 420 g/l: EU limit value for this product (cat. IIB.D) in ready for use settings is max. 420 g/l. This product has a VOC-content of less than 420 g/l.

The actual VOC-content of the type to be processed may be partially lower than specified through the EU-directive code. The correct addition of the additive has no influence on the modified clear-coat or filler data.

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Security Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE