

## :: Auto Mask

handy masking film incl. adhesive tape

### CHARACTERISTICS

CS Auto Mask is a 2 in 1 pre-folded masking film with integrated masking tape.  
Can be used for oven and IR-drying:

- 60 minutes at 60°C
- 30 minutes at 110°C

### APPLICATION

This time saving 2 in 1 masking system can be used for quick covering of complete cars or parts as windows, shock absorbers, bumpers etc..

### PRODUCT DATA

#### MATERIAL DATA:

#### **Film**

Type of film: HDPE

Colour: Transparent (Matt)

Statically charged: Yes

Thickness (µm): 8

Tensile strength, MD (N/mm<sup>2</sup>): 60

Elongation, MD (%): 250

Yield, MD (N/mm<sup>2</sup>): 45

#### **Self-Adhesive Tape**

Carrier: Saturated smooth crepe paper



03/2021

Adhesive: Natural rubber  
Clean removability: 2 Days  
Total thickness ( $\mu\text{m}$ ): 125  
Adhesion to steel at RT (N/25mm): 6.5  
Tensile strength, MD (N/25mm): 87.5  
Elongation, MD [%]: 9

## PRECAUTIONS

Recommended storage and processing conditions:

### Storage time:

12 month from date of delivery in closed original container. Avoid exposure to UV-radiation.

Store in a cool and dry place away from sunlight and direct heat sources.

## SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE