

:: Carbo Putty

polyester carbon putty - transparent

CHARACTERISTICS

Carbo Putty is a transparent polyester putty for carbon parts.

- adhesion on carbon grounds (Polyester / Epoxy - carry out a test beforehand)
- high filling capacity
- very even paint flow
- easy, pore-free application
- super easy sandability
- transparent
- UV-resistant - no yellowing

APPLICATION

Because of its good properties as fill and fine putty Carbo Putty can be used universally.

PRODUCT DATA

MATERIAL DATA

Viscosity at 20°C: paste-like

VOC-content : 2004/42/II B (b) (250): <250 g/l

Colour: transparent

HANDLING

Surface:

The surface must be clean, dry and grease free.

Mixing instructions:

Add 2 - 2,5 % by weight MEKP hardener.

The components should be mixed thoroughly, otherwise there may be a higher sensitivity to moisture.

Pot-life:

At + 20°C room temperature, 10 minutes

Reaction temperature:

Minimum +5°C

Application:

Filling

Hardening time:

Object temperature 20 °C: 60 - 120 minutes

Object temperature 60 °C: 20 minutes

Sanding:

After the specified drying time.

Pre-sanding: dry - with P 240 - P 360

Re-sanding: dry - with P 400 - P 600

Reworking:

You can use the following CS products after filling with Carbo Putty:

Carbo Spray, 2K Epoxy High Speed Primer, 2K Filler VOC 540, 2K Carbo Clear

Vario Filler, Wet on Wet Filler, 1K Filler

Storage:

Approx. 6 month at +18°C - +20°C in closed original container.



03/2021

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE