

::: Dust Keeper

floor dust binding agent

CHARACTERISTICS

Dust Keeper is a waterbased, sprayable floor coating designed to collect and contain airborne dust commonly found in paint booths.

When applied to booth or shop floors, Dust Keeper keeps dust down onto floors and off painted surfaces, so you get clear paint work. After painting, simply sweep up the collected dust and overspray then reapply Dust Keeper. With Dust Keeper there is no need to wet down the floor of a booth to control contaminates. This eliminates unwanted humidity, wet slippery floors and potential rust damage caused by continuously wet booth walls. Dust Keeper also helps reduce overspray build-up on floors and grates.

PRODUCT DATA

Material data:

Form: Liquid

Colour: Transparency

Smell: Not characteristically

pH value: 7,5 - 8,5

Density: 1 g / cm³ (20°C)

Application: approx. 70 - 80 m² per litre

Packaging: Can

Contents: 5 and 20 litres

Contents: Frost-protected

Storage stability: 2 years



03/2021

HANDLING

Application:

Dust Keeper is most effective when used on a clear non-oversprayed floor. Use a pump spray to apply a light coat of Dust Keeper on the clean floor. If floor has overspray build-up, apply heavier coats of Dust Keeper more often. Maintenance: Sweep out collected contaminants as needed, reapply other

car. Removal: If necessary, hose out collected contaminants with water, this will also remove Dust Keeper. Squeegee or force dry, repeat application.

Effectiveness: Up to three paint cycles

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions.

In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE