

# Easy Mask II

Masking Film, transparent / Roll

V01  
05/2026

## Description

- Standard transparent masking film

## Area of application

- For all necessary masking work in a paint shop
- Masking film for vehicles and vehicle parts

## Benefits

- The film is stored in a dispenser box, protected from dust
- The film is transparent to ensure precise cutting
- Due to its static properties, the film adheres firmly to the vehicle
- The film provides paint adhesion
- Easy to cut
- 120°C temperature resistance

## Product Data

### Material data

Material:	HDPE + LDPE
Dimensions	4 x 150 m / 5 x 120 m
Film thickness:	10 µm
Core diameter:	Ø 38 mm
Colour:	Transparent with 'TOP/OBEN' print (top side)
Shelf life:	12 months when stored correctly in the original carton

## Handling

### Application:

Before use, ensure that the marked side of the film (TOP / OBEN) is facing upwards/outwards. Position the film behind the vehicle and pull it completely over the vehicle to be covered. The film can then be spread out and cut to size.

When repositioning the film, we recommend not pulling it tightly over the vehicle, but lifting the film slightly and using a wave-like motion to draw air underneath it. The film can then be repositioned on the vehicle quickly and easily.

Do not apply the protective film to wet or dirty surfaces.



### Storage and transportation conditions

12 months when stored properly in the original carton (do not store on concrete floors).

The recommended storage temperature should be between 10–20 °C. Direct exposure to UV radiation should be avoided.

# Easy Mask II

*Masking Film, transparent / Roll*

V01  
05/2026



## **Safety issues**

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

© VOSSCHEMIE