

V01 07/2018

CS Elastic Additive

:: CHARACTERISTIC

The Carsystem Elastic Additive is a special additive to improve the flexibility of 2K-solvent borne fillers and clear coats. It enhances the adhesion and elasticity and thus prevents the formation of cracks.

The Carsystem Elastic Additive is perfectly suited for car refinish coatings which are applied on plastic or metal parts and exposed to stone impacts and strains.

: PRODUCT DATA

Colour:	transparent
Density:	1.06 g/cm ³
Durability:	18 months
Mixing ratio:	20% on component-A
Suitable for:	all Carsystem Clear Coats & Fillers
NOT suitable for:	1K Filler & Eco Plus Clear Coat

:: HANDLING

Add 20% of the Elastic Additive on component A (filler or clear coat). Afterwards add the hardener in the indicated ratio e.g. 4:1 = 100ml filler / 20ml Elastic Additive / 30ml hardener (Elastic Additive is calculated to component A) and if necessary add the suggested amount of thinner. Then mix thoroughly.

NOTE: Higher thickness and longer drying time of the coating may be expected while using Elastic Additive.



V01 07/2018

:: SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, expect we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery terms and conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE

Page 3 of 4