

:: Etch Primer

primer

CHARACTERISTICS

Etch Primer is an adhesion primer for metal surfaces. It has excellent adhesion to all steel, zinc and aluminium surfaces. Etch Primer is easy to use and dries rapidly.

APPLICATION

Etch Primer is used as an adhesion primer for steel, zinc and aluminium surfaces. It is suitable for spot and partial repairs. Suitable to isolate bare metal and provide rust protection.

Etch primer doesn't provide 100% adhesion for waterborne paint, in this case apply 1K or 2K Filler before applying waterborne basecoat.

PRODUCT DATA

MATERIAL DATA V.O.C.: 709.6 g/l

Packaging: 400 ml aerosol can

Colour: grey

Drying Time: 15 min. at 20 °C

Storage Life: At least 24 months in the closed original container



Telefon Telefax E-Mail +49 (0) 4122/717 -0 +49 (0) 4122/717-158 info@vosschemie.de www.carsystem.org www.vosschemie.de





HANDLING

The surface should be clean, sanded, dry, grease and dust free. Clean the damaged area with a silicone remover. Shake the can thoroughly for 2 minutes before use. Apply Etch Primer in several thin layers.

PRECAUTIONS

Do not overpaint with polyester products!!! Wear a respirator during application!!!

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE

