

# Fine Line Tape Blue

*paint line tape*

V03  
03/2025

## Description

- Heat-resistant film masking tape / fine line tape for high-quality and precise paint lines
- Thanks to the tape's exceptional flexibility, it adheres well to both curves and long, straight lines

## Area of application

- Premium masking tape for multi-colour and design paintwork
- Suitable for application on painted metal, rubber, glass, or chrome parts

## Benefits

- Highly flexible
- Produces low, clean paint edges
- Heat resistant up to 155°C
- Water resistant
- Excellent resistance to solvents

## Application advice

- Store only in clean, dry, well-ventilated areas
- Storage temperature must be between +10°C and +30°C

## Product Data

### Material data

Backing:	Polyvinyl chloride film
Standard roll length:	33 m
Widths:	3, 6, 9, 12, 19 mm
Total thickness:	0.13 mm
Colour:	Blue
Adhesion to steel:	16.42 N/100 mm
Adhesion to steel (after 20 min dwell):	26.30 N/100 mm
Tensile strength:	210 N/100 mm
Elongation at break:	100%
Service temperature range:	0°C to +155°C
Solvent resistance:	Excellent
Shelf life: 1 year when stored at temperatures between +10°C and +30°C	
<i>Protect the product from frost.</i>	

## Handling

The application temperature should be between +15°C and +30°C. The surface must be clean, grease-free, and free of dirt. Avoid touching the adhesive surface, as this may compromise adhesive performance. To achieve optimal adhesion, the initial application pressure should be applied with maximum force. Maximum adhesion is reached after a curing period of 24 hours at +23°C.

# Fine Line Tape Blue

*paint line tape*

V03

03/2025



## Safety issues

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

© VOSSCHEMIE