

# **CS FINISH Quadra Pad C10**

Polishing Pad 09/2014

## :: CHARACTERISTICS

Original polishing disc with slitted foam surface, which leads to a higher removal rate and low heat generation. The red intermediate layer provides added stability and even removal during polishing. The **FINISH Quadra Pad C-10** is ideally suited for applications on fresh paintwork.

### :: APPLICATION

This pads works best with the CS POLISH C-10 strong.

# :: PRODUCT DATA

# **MATERIAL DATA:**

Density: 38-44 kg/m³
Tensile Strength: >500 kPa
Elongation: >80 %
Hardness: >30 kPa
Cell qty.: 17-23 ppi

#### **SAFETY ISSUES**

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to



#### **TECHNICAL DATASHEET**



prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE