

## ::: Glas weiss

polyester fibreglass reinforced putty - white

### CHARACTERISTICS

White fine fibrous fibreglas putty.

- finer fibres
- neutral colour
- easier spreading behaviour
- easier to apply
- easier to sand
- for repairing small rust spots
- Only for use on steel-bases, GRP and wood.

### APPLICATION

Suitable for repairing of GRP, for filling deep uneven areas and for application in the repair of small rust spots.

### PRODUCT DATA

#### MATERIAL DATA

- **Delivery viscosity at 20°C:** paste-like
- **VOC content:** 2004/42/IIB (b) (250) < 250g/l
- **Colour:** white

### HANDLING

#### **BASE:**

The base must be clean, dry and grease-free.

**DOSING:**

Addition of 2-3 % by weight hardener paste white.

**Overdosing**

of the hardener paste is to be avoided. Bleeding-through and colour changes in the finishing coat might be the result.

**POT-LIFE:** At +20°C room temperature, 4-5 minutes.

**REACTION TEMPERATURE:**

At least +5°C.

**APPLICATION:**

Spread on with a spatula

**DRYING TIME:**

Air drying at +20°C room temperature, 20 - 30 minutes.

**SANDING CHARACTERISTICS:**

Following to the given drying times.

**As filling putty**

First sanding - dry with P80 - P120

Re-sanding - dry with P120 - 240

**REWORKING:**

The glasfibre putty can be gone over with the following CS products:

All Multi putties, all Non-Multi putties, Elastic green, white or beige, Spray and Spray Plus.

**STORAGE:**

Ca. 6 - 8 months at 18 - 20° C in closed original container



03/2021

## **SAFETY ISSUES**

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE