



Glass fibre fabric

Glass fibre fabric

:: DESCRIPTION

- Glass fibre fabric
- Weight: 300 g/m²

:: AREA OF APPLICATION

- For covering small holes in the surface on non-bearing parts

:: BENEFITS

- Simple handling for round parts

:: APPLICATION ADVICE

- Usable with polyester repair resin

:: PRODUCT DATA

Technical data

Product description:	Woven Roving
Weight:	300 g/m ² (+/- 8%)
Glass type:	E-Glass
Sizing:	Silane (UP, VE resin compatible)
Warp:	5,0 thr/cm – 300 tex
Weft:	4,6 thr/cm – 300 tex
Weave:	Plain 1/1
Selvedge:	Leno thread, cut edges
Storage:	Material should be stored in original packaging, away from humidity, in well-ventilated rooms, at a moderate temperature.



Glass fibre fabric

Glass fibre fabric

:: SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, expect we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery terms and conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE