

## ::: KS-100

underbody protection bitumen

### CHARACTERISTICS

Brushable Underbody Protection is a thixotropic bitumen-resin mixture that protects vehicle underbodies from corrosion. This product offers long-term protection from rocks, road salt, etc. and reduces road noise.

### APPLICATION

Uses:

Long-term corrosion preventative for underbody treatment of all types of vehicles.

### PRODUCT DATA

Material data:

Packaging: 1000 mL; 2000 mL

Color: Black

Specific gravity: 1.3 g/mL

Dust-dry (20°C): Approx. 2 hours (50µm wet)

Can be thinned with: Mineral spirits

The drying time depends on the layer thickness and ambient conditions (ca. 12 hours).

Solids content: Ca. 77%



03/2021

## HANDLING

The underbody must be clean, dry, and free of grease, oil, and rust. Shake container well before use. Apply at a temperature of 15°C.

## SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE