

::: KS-250

cavity protection ML

CHARACTERISTICS

This product is designed to protect hollow cavities in your vehicle from corrosion. It has a wax-like consistency that leaves an elastic film on the underbody once the solvent evaporates. Its ability to flow into tight spaces, repel water, and adhere well to metal will provide reliable rust protection for several years. Cavity Protection ML Spray can withstand even the toughest ambient conditions, such as long-term exposure to salt water.☒

APPLICATION

Protection of all body cavities on the vehicle. Its ability to flow into tight spaces makes it ideal for difficult-to-reach spots as well.

PRODUCT DATA

Material data:

Packaging: 500 mL container

Color: brown - transparent

High melting point: 160°C

Specific gravity: Approx. 0.679 kg/l

Shelf life: At least 5 years

Solids: 11 – 12 %

Flash point: < 23° C

Drying time: Approx. 5 hours

.



03/2021

HANDLING

The surfaces to be treated must have the worst of the rust removed beforehand. They should also be dry and free of grease, oil, and dust. Shake the container well before using and apply product at room temperature (15°C – 30°C). Spray an extra-thick layer on problem zones like corners, edges and weld seams.

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE