

CS Masking Film green

Masking Film

:: CHARACTERISTIC

The Carsystem Masking Film green is a paint-adhesive masking film for covering vehicles, SUV's and vans. It is static and infrared resistant up to 110°C. In addition, it is easy to cut, waterproof and resistant to solvents.

The masking film is packed in a box and can be handled directly out of the box.

:: APPLICATION

The Carsystem Masking Film green can be used for all masking work in the bodyshop. Not suitable for residual moisture.

:: PRODUCT DATA

Technical data

Dimensions:	4x150m, 4x300m, 5x120m, 6x100m
Thickness:	11µ
Heat resistance:	up to 110°C
Storage life:	12 months from date of manufacture

:: HANDLING

Recommended conditions for storage and processing:

The processing features are strongly influenced by the storage conditions. Therefore we recommend a relative humidity of 30 - 90% and a storage temperature of +20°C.

Storage time: 12 months from date of manufacture in a closed original container. Influence of UV radiation is to be avoided.

This technical information has been given to the best of our knowledge. The above mentioned standards are average values and no granted assurance of special properties. This statement is limited to the material as it leaves the company and does not include possible modifications by conversion and/or handling after dispatch.

:: SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, expect we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery terms and conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE