Masking Paper Master II

masking paper



V03

Description

Masking Paper Master II is a high-quality kraft paper (40 g/m²) with good density and puncture strength. Masking Paper Master has increased water resistance to stand up to the primers and acrylic and clear coat paints used today, as well as a smooth, non-porous surface on one side to prevent the paper fibers from pilling. Mechanical processing of the paper fiber creates a barrier that seals the surface without the use of PFAS. The product is also solvent-resistant.

Area of application

Masking Paper Master is used in vehicle paint shops. It serves to cover and protect body surfaces and panels while other areas of the vehicle are being painted.

Product Data

Material data

Paper type: Natronkraft paper
Paper base weight: 40 g/m²

Surface: Free of PFAS. Sealed by mechanical processing of the paper fiber.



Safety issues

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

© VOSSCHEMIE