

:: Masking Paper Top II

masking paper

CHARACTERISTICS

.

Masking Paper Top II is a kraft paper (40 g/m²) with good density and puncture strength. Masking Paper Top II has increased water resistance and a non-porous surface to prevent the paper fibers from pilling.

APPLICATION

.

Masking Paper Top II is used in vehicle paint shops. It serves to cover and protect body surfaces and panels while other areas of the vehicle are being painted.

PRODUCT DATA

.

Paper type: Natronkraft paper

Paper base weight: 40 g/m²

Dimensions:

- 20 cm x 450 m
- 60 cm x 450 m
- 90 cm x 450 m
- 120 cm x 450 m
- 150 cm x 450 m



03/2021

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Copyright VOSSCHEMIE