

# :: Master Tape II

masking tape

## **CHARACTERISTICS**

CARSYSTEM® Master Tape II is a slightly creped, flexible masking tape with excellent elongation characteristics and a high initial adhesion strength. This product is suitable for masking jobs for wet sanding as well as for solvent-based or water-based application of color paints with subsequent drying in a drying booth. It will adhere to painted metal, rubber, glass or chrome parts. After the vehicle leaves the drying booth, CARSYSTEM® Master Tape II comes off cleanly and leaves no residue.

### **APPLICATION**

CARSYSTEM® Master Tape II is a professional-quality masking tape for reliable overspray protection during application processes with subsequent booth drying up to 120°C.

### **PRODUCT DATA**

**MATERIAL DATA:** 

(Average values) Backing material: Crepe paper

Total thickness: 150 µm

Adhesive power on steel (N / 25 mm): 5.4

Tensile strength (N /25 mm): 110

Elongation at tear: 9 % Heat resistance: 120 °C

stability in storage (20°C / 50% RH): 18 month

**Dimensions:** 

Standard roll length: 50 m



Telefon Telefax E-Mail +49 (0) 4122/717 -0 +49 (0) 4122/717-158 info@vosschemie.de www.carsystem.org www.vosschemie.de





Widths: 15, 19, 25, 30, 38, 50 mm

#### **SAFETY ISSUES**

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply. Directions for handling and waste disposal are in our Security Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE

