

MULTI BLUE RAPID CHANGER SF

2K polyester general purpose lightweight *putty*, styrene-free

V02
09/2025

Description

- Polyester multifunctional putty
- Styrene-free
- Multi adhesion
- Colour change during the curing time from blue to grey

Area of application

- For filling small to deep imperfections, dents and scratches.

Benefits

- Styrene-free
- Pore-free and easy to apply due to the creamy texture
- Faster drying time
- Colour change during the curing time from blue to grey

Product Data

Material data

Viscosity at 20°C: Creamy paste
VOC-content: 2004/42/IIIB (b) (250) <250g/l
Specific weight: 1,3 g/cm³
Colour: blue with a colour change to grey

Handling

Surface:

- The surface must be clean, dry and free of greases.
A good adhesion is reached on all roughly sanded surfaces.

Hardening time:

- At a room temperature of 18-20°C, 12 minutes are normally required before the filler can be sanded.

Mixing instructions

- No more than 2-3 % (by weight) of BPO hardener paste should be added to 100 parts of polyester filler.
- Excessive amounts of BPO hardener paste can cause a colour change of the topcoat.

Sanding:

Following the specified drying time.

First sanding: dry with P150 – P180
Re-sanding: dry with P240 - P320

Pot-life:

- At a room temperature of 20°C the pot life is 4 minutes.

Reaction temperature:

- at least +10°C

Storage:

- 9 months at 18 - 20° C in closed original containers.
- Store in a cool, well-ventilated area away from direct sun light, incompatible materials and ignition sources. Prevent unauthorized access.

Steel	Aluminium	Galvanized tin	GRP	Plastic	2K Polyester putty	Wood
√	√	√	√	X	√	√

MULTI BLUE RAPID CHANGER SF

2K polyester general purpose lightweight filler, styrene-free

V02

09/2025



Storage and transportation conditions

Allow the product to reach the recommended application temperature naturally (avoid rapidheating/ cooling). It is not recommended to apply the product at a temperature below 18 °C. Low application temperature changes the coating's properties and may impair the visual.

Storage: approx. 9 month at 18 -20 °C in closed original container



Safety issues

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

© VOSSCHEMIE