

Paint Arrestor II

Paint mist separator

V01
07/2025

Description

- Paint mist separator and paint filter for paint booths
- Glass fibre base with elastic fibre structure
- Temperature resistant up to 120°C
- Thickness: 3 Inch (+/- 75 mm)

Area of application

- Paint filter for booths
- Separation of paint mist

Benefits

- High performance filtering

Product Data

Technical data

Paint mist separation efficiency*: ca. 93 %

Nominal flowrate: 0,7 - 1,5 m / s

Maximum temperature: 120 °C

Material thickness: +/- 75 mm

Material weight (roll) 240 g/m²

Dust holding capacity 3200 – 3600 g/m

* The degree of separation depends on the type of paint, atomisation or ambient conditions such as temperature or pressure in the booth.



Safety issues

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

© VOSSCHEMIE