

Polish X8000

High-Performance cutting compound

V01
03/2026

Description

- Water-based Anti-Hologramm Polish

Area of application

- For the easy and fast removal of holograms and enhancement of deep gloss

Benefits

- Very fine abrasive particles for the safe removal of fine scratches and holograms
- Extremely high gloss level
- High efficiency
- Does not dry out
- Silicone-free
- Water-based

Application advice

We recommend the CS Polishing Pad X8000 AH.

The fine abrasive particles of CS Polish X8000 remove light scratches and holograms in a single step.

After 15–20 seconds, all scratches and holograms are removed.

The abrasive particles are fully refined and improving the surface up to an extremely deep gloss finish.

Product Data

Technical data

Shelf life: 24 months from the date of manufacture when stored properly in the original unopened container.

Product must be protected from frost.

Revolutions Polishing machine: Rotary: 600 – 1500 U/min.

Orbital: 2000 – 8000 U/min

Surface

Suitable for all glossy clear coats in the automotive sector.



Safety issues

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

© VOSSCHEMIE