

ProFlex Saturn

75 mm - no holes

CHARACTERISTICS

The Carsystem ProFlex Saturn 75 mm is perfectly suitable for sanding primers, fine sanding of fillers, as final sanding step before applying the base coat, for matting clear coats, sanding the transition zone and for sanding dust inclusions and imperfections in the painted surface.

APPLICATION

- Perfect for dry sanding
- For removal of dust inclusions and imperfections in the paint surface
- Uniform and shallow scratch pattern
- High removal rate
- Provides optimal transition zones
- Excellent durability
- No more wet sanding

PRODUCT DATA

Type: Sanding discs

Size: Ø 75 mm

Carrier material: Film

Bonding: Special treated corundum in modified resin paper: integrated

Abrasive grit type: Special treated corundum

Dispersion: Half open Hole system: No holes

Grits: P 800, P 1500, P 2000



Telefon Telefax E-Mail +49 (0) 4122/717 -0 +49 (0) 4122/717-158 info@vosschemie.de www.carsystem.org www.vosschemie.de





HANDLING

The CS ProFlex Saturn 75 mm can be processed by machine. We recommend the following additional products:

- Processing by machine with the CS ProFlex Interface Pad Soft 75 mm 154.294
- Processing by machine with the CS Finish Sander 143.388

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Security Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE

