



:: Pump Spray

pressurized atomizer

CHARACTERISTICS

CS Pump Spray is a compressed air sprayer made of impact resistant plastic with a very fine spray pattern and a high output.

Quick and easy filling of the spray bottle.

APPLICATION

For evenly and constant atomization of many solvent borne fluids. Solvent resistant due to Viton seals.

To identify the contents of the filled bottle, simply plug the different colored coding rings, CS Coding Caps on.

PRODUCT DATA

MATERIAL DATA

Plastics: PA Gaskets: FKM Steels: V2A

Fill quantity: 0,9 I max.

Operating pressure: 3 bar / Safety valve

Colour: White, translucent

Pressure build-up in the liquid container by pumping. Regulation of the spray mist by turning the nozzle nut.



Telefon Telefax E-Mail +49 (0) 4122/717 -0 +49 (0) 4122/717-158 info@vosschemie.de www.carsystem.org www.vosschemie.de





Suitable for the following fluids containing solvents:

- Carsystem Silicon Remover Mild
- Ethyl chloride
- Glycerol
- Soda (sodium carbonate)
- Toluene A568
- Detergent dissolved in water
- Hydrogen peroxide diluted
- Xylene

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Emplyers Liability Insurance Association for the chemical Industrie.

Copyright VOSSCHEMIE

