

Red Tape

Masking Tape

V01
01/2026

Description

- Water- and solvent-resistant masking tape with natural rubber adhesive
- Temperature-resistant all-purpose masking tape for all common painting applications

Area of application

- Masking tape for all common painting applications
- Suitable for bonding to painted metal, rubber and glass
- Suitable for indoor use and for short-term outdoor masking applications with clean removal within 3 days

Benefits

- Temperature resistance up to 110 °C
- Particularly small roll core (Ø approx. 2.5 cm) – practical and space-saving handling
- Unique visibility (red colour)
- Easy removal without adhesive residue
- Drying cycle at 90 °C (1 hour) – 110 °C (30 minutes)
- Excellent adhesion and fast bonding
- 3 days UV resistance

Product Data

Material data

Backing material:	Saturated crepe paper
Adhesive:	Natural rubber
Standard roll length:	50 m
Widths:	18 mm, 30 mm, 48 mm
Core diameter:	Ø approx. 2.5 cm
Total thickness:	0.13 mm
Tape colour:	Red
Temperature resistance:	>110 °C
Operating temperature range:	0 °C to +110 °C
Adhesion to steel:	2.3 N/cm
Tensile strength:	42 N/cm
Elongation at break MD:	8 %
Shelf life:	1 year when stored at temperatures between +10 °C and +30 °C

Protect the product from frost.

Red Tape

Masking Tape

V01

01/2026



Safety issues

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

© VOSSCHEMIE