

:: Spotblender

spot repair blender

CHARACTERISTICS

- Blender for spot repair coatings
- Easy and quick application
- Very good solving properties between new and old coat
- Effect is immediately visible and can be influenced directly
- Soft transition zones
- minimal polishing work
- Ready to use

APPLICATION

Spot repair

PRODUCT DATA

Specific weight: 0,9 g/cm³

Colour: transparent

Storage conditions: minimum 12 months in closed original container

HANDLING

Substrate:

The substrate in the transition zone must be matted in advance.



Preparation:

Fill the Spotblender in the paint spraying gun used before for the clearcoat. Shake well and applicate. Alternatively fill in a small bucket and blend manually with it.

Handling:

Apply immediately after the use of clearcoat or topcoat onto the transition zone of the substrate to be blended. Apply 2 - 3 light spray passes onto the transition zone until a homogenius transition is obtained. No flash-off time required.

Processing tools:

HVLP Minijet Spraygun: 0,8 - 1,0 mm

Gravity spray gun: 1,2 - 1,3 mm

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.



Telefon Telefax E-Mail +49 (0) 4122/717 -0 +49 (0) 4122/717-158 info@vosschemie.de www.carsystem.org www.vosschemie.de





Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE

Telefon Telefax E-Mail +49 (0) 4122/717 -0 +49 (0) 4122/717-158 info@vosschemie.de