

:: Spritzspachtel

spray filler

CHARACTERISTICS

Aerosol Spray Filler is a fast-drying acrylic filler to even out small imperfections, scratches, and sanding marks. This product creates a smooth surface on filled substrates for subsequent painting.

APPLICATION

For evening out small imperfections, scratches, sanding marks, etc. on filled surfaces.

PRODUCT DATA

Material data:

Color: Gray

Theoretical coverage: 400 ml = 0.4 – 0.8 m² (depending on how thickly it is applied)

Sanding time (20°C): Approx. 1 hour

Recoat time (20°C): Approx. 2-5 minutes

HANDLING

The surface must be dry, clean, free of grease and oil, and sanded. Shake the spray can well for at least 3 minutes before use. Spray from approx. 25-30 cm (10-12 in) away from the surface. Apply the aerosol spray filler in several thin coats. Wait 2-5 minutes between each thin coat. Once the filler is dry, apply primer, and then paint. Sand a rough finish into the aerosol spray filler if you want to apply paint directly over the filler.



03/2021

PRECAUTIONS

Contents under pressure. Do not store at temperatures above 50°C.

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE