

::: Top Tape

masking tape

CHARACTERISTICS

Top Tape is a slightly creped masking tape with good elongation characteristics. This product is excellent for masking vehicles prior to the application of solvent-based paints and drying in a drying booth. It will adhere to painted metal, rubber, glass or chrome parts. After the vehicle leaves the drying booth, Top Tape comes off cleanly and leaves no residue.

APPLICATION

Standard masking tape for reliable overspray protection during application processes with subsequent booth drying up to 80°C.

PRODUCT DATA

MATERIAL DATA:

(Average values)

Backing material: Crepe paper

Total thickness: 0.14 mm

Adhesive power on steel (N / 10 mm): 7.0

Tensile strength (N /15 mm): 90

Elongation at tear: 10 %

Heat resistance: 80° C

Dimensions:

Standard roll length: 50 m

Widths: 15, 19, 25, 30, 38, 50 mm



03/2021

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE