

:: UNIFLEX Glas Fast-Primer

moisture curing glass ceramic primer

CHARACTERISTICS

Uniflex Glas Fast-Primer is a black Primer specifically designed for the ceramic band on vehicle glass. It ensures the complete protection of the adhesive by creating a barrier against harmful UV rays which can lead to the degradation of the adhesive. It is also an adhesion promoter. To be used in conjunction with Uniflex Glas Fast-Cleaner.

APPLICATION

The surfaces to be treated must be perfectly clean, dry, dust and grease free. Application of Uniflex Glas Fast-Primer can only take place once the thorough cleaning of the bonding area with, Uniflex Glas Fast-Cleaner has been completed. Using a wire felt applicator, apply a thin even layer of Uniflex Glas Fast-Primer to the ceramic band and leave to dry for 15 minutes.

PRODUCT DATA

Density at 20°C: 0.93 +/- 0.02 g/ml

Drying time: 15 min.

Odour: Characteristic of solvent

Appearance: Black liquid

Tack free time: Less than 30 minutes

PRECAUTIONS

Uniflex Glas Fast-Primer can be stored for 12 months in it's original packing at 5° - 25°C.



03/2021

Keep away from heat sources.

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE