

WR-Lifting Tape Premium

Masking tape with plastic edge - perforated

V03
10/2025

Description

- Special masking tape made of crepe paper with high-strength, perforated plastic edge (9 mm + 11 mm)
- Waterproof and heat-resistant up to 110 °C
- Innovative tear-off system "from plastic to tape side" for clean handling

Area of application

- Covering window seals, shaft strips, and sealing lips
- Protection of front and rear lights and indicators during painting work

Benefits

- 2-in-1 component: tape + plastic edge perfectly combined
- Perforated edge allows easy, precise tearing off to the requested length
- Plastic edge sits under the rubber and is then "invisible" – ensures particularly clean lines

Product Data

Material data

Colour:	Beige
Carrier:	Lightly creped special paper + perforated plastic strip
Adhesive:	Cross-linked, modified natural rubber
Insertion bar:	Polyester film (0.125 mm)
Adhesive strength:	2,4 N/cm 6,0 N/25mm
Temperature resistance:	short-term up to 110 °C
Special features:	Water-based paint stable
UV resistance:	Limited
Weather resistance:	Limited
Processing temperature:	Recommended > 5°C
Shelf life:	Approx. 12 months (dry, +5°C to +25°C, UV-protected)

Dimensions

Roll length:	10 m
Roll width:	50 mm
Polyester film:	9 mm + 11 mm
Total thickness:	0,25 mm
Core diameter:	76 mm

Protect product from frost.

Handling

- Tear open the tape along the perforated plastic edge
- Position the plastic edge neatly under the rubber or headlight edge
- After painting and drying: peel off – ideally without leaving any adhesive residue and with a straight edge

WR-Lifting Tape Premium

Masking tape with plastic edge - perforated

V03
10/2025



Safety issues

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

© VOSSCHEMIE