

:: Plastic Primer

plastic primer

CHARACTERISTICS

- Excellent adhesion on all plastic car parts, both interior and exterior, e.g. bumper, tuning-parts, outside mirrors
- High elasticity
- Easy and quick application
- Very time-saving application
- Very fast drying
- High productiveness
- Re-Coat able after 10 min. air drying, e.g. with CS – 1K Primer, 1K High-Build Primer, CS-2K Fillers, RAL-acrylic spray paint or pre filled basecoat

APPLICATION

- Adhesion-Promoter on all plastic car-parts, interior and exterior

PRODUCT DATA

Specific weight: 0,77 g/cm³

Shelf life: minimum 2 years

V.O.C.: Colour: transparent

HANDLING

SUBSTRATE:

- PP, PP/EPDM, ABS, SAN, PC, PA, PUR-RIM, R-TPU, PPO, PBT, PUR-foam, UP-GF plastics
- Clean surface with CS-Plastic Cleaner antistatic



05/2020

APPLICATION:

- 1 light spray pass
- Air drying 10 min./20°C
- Re- coat able after 10 min/20°C

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Thin product contains isocyanate and can cause lung or breathing as well as hypersensitivity reaction. Before using or working with coatings material that contains isocyanate, all safety information's on the can label and the material safety data sheet must be read. Individuals with lung or breathing problems or prior reactions to isocyanate must not be exposed to vapour or spray mist.

The use of a respirator mask is necessary!

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Notice EU-safety data sheet as well as handling and warning notices on the label.



05/2020

Copyright VOSSCHEMIE